

▼ FICHES INDUSTRIELLES IP44 & IP67



MULTIMAX SERIES
Protected straight plugs
wiring low voltage
IP44



MULTIMAX SERIES
Watertight straight plugs
rapid wiring
low voltage
IP67



new MULTIMAX SERIES
Watertight straight plugs 63A
rapid wiring
low voltage
IP67



CEE SERIES
High performance **90° angled watertight appliance inlet**, very low voltage
IP67



CEE SERIES
High performance 90° angled protected appliance inlets, low voltage
IP44

▼ PROLONGATEUR IP44 & IP67



MULTIMAX SERIES
Protected straight connectors,
rapid wiring and low voltage
IP44



MULTIMAX SERIES
Watertight straight connectors,
rapid wiring
low voltage
IP67



new MULTIMAX SERIES
Watertight straight connectors 63A
rapid wiring low voltage
IP67

▼ PRISES INDUSTRIELLES IP44 & IP67



CEE SERIES
Watertight high performance **flush-mounting straight socket-outlets**
low voltage - **IP67**



CEE SERIES
Straight high performance and low voltage **protected flush-mounted socket outlets**
IP44



CEE SERIES
Watertight angled high performance and low voltage **flush-mounted socket-outlets**
IP67



CEE SERIES
Watertight angled high performance and low voltage **flush-mounted socket-outlets** **IP67**



▼ COFFRETS DE DISTRIBUTION



topTER 102
In thermoplastic with interlocked
socket-outlets




topTER 102
In thermoplastic with fixed sockets



TAIS 103
In GRP material with interlocked
socket-outlets

▼ COFFRETS DE CHANTIER



▼ APPLICATION MARINE IP66



NAVE SERIES
Watertight UNAV 2181 junction boxes with blind walls, with terminal block, in thermosetting (GRP) material
IP67



NAVE SERIES
Watertight UNAV 1398 junction box in brass painted marine grey, with terminal block and UNAV 1948 cable glands
IP66



NAVE SERIES
Watertight UNAV 2161 junction boxes in brass painted marine grey, with double opposite entry points, together with terminal block and UNAV 1948 cable glands
IP66



NAUTILUX SERIES
UNAV 1398 watertight junction box in solid brass with terminal block
IP66



NAVE SERIES
Watertight UNAV 2162 rotary switches in brass enclosure painted marine grey, together with UNAV 1948 cable glands
250V IP66



NAVE SERIES
Watertight UNAV 2162 two-way switches in brass enclosure painted marine grey, together with UNAV 1948 cable glands
250V - IP66



NAUTILUX SERIES
UNAV 2162 watertight rotary control switch in solid brass enclosure
250V - IP66



NAVE SERIES
Watertight UNAV 2166 wall-mounted socket-outlets in brass enclosure painted marine grey, with UNAV 1948 cable glands
250V - IP66



NAVE SERIES
Watertight UNAV 1435 socket-outlets in brass enclosure painted marine grey, with UNAV 1948 cable glands
250V - IP66



NAVE SERIES
Watertight UNAV 1437 plugs with ring-nut and rubber protection sleeve
IP56



Brass sirens



Brass bells



NAVE SERIES
Watertight large lighting fixture type UNAV 2139 brass painted marine grey, including tropicalized steel cage
250V - IP66

▼ MATERIEL ANTI-DEFLAGRANT POUR ZONE2



ULYSSE-EX

In thermosetting (GRP) material IP66 / IP67



TAIS-EX

In thermosetting (GRP) material IP66 / IP67



ALUPRES-EX

In aluminium IP66 / IP67



TAIS-Ex SERIES

Watertight wall-mounting blind enclosures with ATEX low cover, in thermosetting (GRP) material IP66 / IP67



TAIS-Ex SERIES

Watertight wall-mounting blind enclosures with ATEX high cover, in thermosetting (GRP) material IP66 / IP67



TAIS-Ex SERIES

ATEX watertight blind enclosures in thermosetting (GRP) material with mounting plate in tropicalized steel plate IP66 / IP67

ALARM-EX



Sirens



Bells



TAIS-MIGNON-Ex SERIES
ATEX switches in watertight wall-mounting enclosure in thermosetting (GRP) material IP66 / IP67



RINO-Ex SERIES

ATEX grey watertight oval lighting fixtures in aluminium alloy RAL 7035, tropicalized steel wire protective cage and glass diffuser 250V - IP65



RINO-Ex SERIES

ATEX grey watertight round lighting fixture in aluminium alloy RAL 7035, tropicalized steel wire protective cage and glass diffuser 250V - IP65



RINO-Ex SERIES

ATEX stainless steel-glass lighting fixtures with white reflector and electromagnetic power supply 230V - 50 Hz - IP66



RINO-Ex SERIES

Stainless steel-glass lighting fixtures, for **emergency** 230V - 50 Hz - IP66

